



METRIX ENGINEERING CO., LTD.

美捷工程有限公司

Unit 102-107, 1/F., Hong Leong Industrial Complex,
4 Wang Kwong Road, Kowloon Bay, Kowloon, Hong Kong
Tel: (852)2811 8876 E-mail: metrix@metrix.com.hk
Fax: (852)2811 9076 Web: www.metrix.com.hk

香港 九龍 九龍灣
宏光道四號
豐隆工業中心
一字樓102-107室

日期: 01-Apr-2019

Type "ME-CTB" Cable Link Box / Tee-off Box 分線箱

- Rate Voltage 額定電壓: 380 / 415V

The enclosures are manufactured from heavy gauge galvanized sheet steel finished with stoved, textured light

- grey (to RAL 7032) polyester-epoxy power coating. 分線箱用厚鉛水鐵片做焗上淺灰色環氧樹脂塗磁
- 2 earthing studs M6 with nuts. M6 水線螺絲
- Flange plate: - insulation plate for "ME-CTB-250 to 800" 上下用絕緣板 (單支線分線箱)
- metal plate for "ME-CTB-250A to 800A" 上下用厚鐵片 (地線分線箱)

Options are available upon request 其他要求亦可訂造: -

- Stainless steel enclosures. 不銹鋼片
- Degree protection 外殼保護程度: - standard IP31 標準 IP31
- higher protection to IP-54 · IP-55 and IP-65 亦可訂造
- Other sizes, colours and current rating. 其他呎吋、顏色及額定電流

Cable Link Box / Tee-off-Box for 1-core Cable 單支線分線箱

Type No. 型號	Main Cable (Max.) 主線			Tee-off Cable (Max.) 分線			Metal Box (mm) 鐵箱		
	Copper Bar. Current Rating 銅巴額定 電流 (A)	Max.Cable Size 最大電線 (sq. mm)	Cable Stud. 線耳呎螺絲 (Ømm)	Copper Bar. Current Rating 銅巴額定 電流 (A)	Max.Cable Size 最大電線 (sq. mm)	Cable Stud. 線耳呎螺絲 (Ømm)	W 寬	H 高	D 厚
ME-CTB-250	250	150	M11	250	10 / 150	M9 + M11	350	400	200
ME-CTB-400	400	300	M20	400	240	M11 + M17	500	500	260
ME-CTB-800	800	2 x 400	M20	800	400	M17 + M20	600	700	260

Cable Link Box / Tee-off-Box for Amoured Cable 地線分線箱

Type No. 型號	Metal Box (mm) 鐵箱		
	W 寬	H 高	D 厚
ME-CTB-250A	350	700	200
ME-CTB-400A	500	1000	260
ME-CTB-800A	600	1200	260

All other data same as above table 其他數據依照前表格

